VARTA
CONSUMER BATTERIES

Data Sheet Lithium Manganese Dioxide CR 2430

Type Number..... 6430

Designation IEC..... CR 2430

System..... Li-Manganese dioxide
Organic Electrolyte

UL Recognition ..... MH 13654 (N)

Nominal Voltage..... 3 V
Typical Capacity C..... 290 mAh



Temperature Ranges	min	max.
Storage	-55°C	70°C
Discharge.....	-20°C	70°C

Dimensions	min	max
Diameter (A)	24,2	24,5
Height (B).....	2,7	3,0

Weight (approx.) ..... 4 g

Typical Capacities (at 20°C)

Discharge Type..... Continuous 24h/d, 7d/w
Load..... 15000 Ω
End Voltage..... 2 V

Time..... 1516 h

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

All Data contained herein is for single cells.
For battery applications, performance data may vary from single cell data, depending on specific battery configuration.

VARTA Consumer Batteries GmbH & Co. KGaA
Alfred-Krupp-Str. 9, 73479 Ellwangen/Germany

Subject to change without prior notice!
Date of issue: 2018-04-16

Phone: (+49) 7961/83-0, Fax: (+49) 800-827-8274